JT300L-P

BATTERY-POWERED ELECTRIC CARRIER ON WHEELS FOR LOADS **UP TO 500 KG***

ZERO EMISSIONS

QUIET

LOW MAINTENANCE





Flatbed with removable sides



Equipment body on 4 wheels for better stability on rough surfaces



Tilting tiller with micro safety switch and automatic return to rest position



Precise handling thanks to the two steering wheels on swing axle


ONESTOP HANDLING





The JT-300LP is a four wheels carrier. The tilting tiller, which acts on the steering wheel, offers great control and easy handling. It has an accelerator operated by the thumb, allowing the use of only one hand. This carrier is ideal for both indoor and outdoor work, in greenhouses and in nurseries. It can push or pull without effort. The 260-liter flatbed is perfect for the rail industry, in Primary care trust centers, in hotels, in greenhouses and nurseries, for gardening and in livestock paddocks.












FEATURES

Equipment body	4 wheels
Driving wheels on differ	ential Garden type
Driving control type	Tiller
Accelerator	Butterfly type
Battery charger	External, 13A High Frequency
Dashboard display JT30	OL-P Remaining battery charge Equipment failures Hour meter
	OL-S Remaining battery charge OL-E Remaining battery charge
Parking brake	Electromagnetic
AGM batteries	2 x 12V/85 Ah C20
Electric motor JT300 JT300 JT300	L-S 24V / 900 Watt S1.
Product net weight	from 173 kg abt

PERFORMANCES

Loading capacity on flat surfaces	* JT300L-P JT300L-S JT300L-E	500 kg 400 kg 300 kg
Max gradient*		20%
Forward speed:		
Fast		5 Km/h abt
Slow		2,5 km/h abt
Reverse speed:		
Fast		3 Km/h abt
Slow		1,5 Km/habt
Battery recharging time		8 hours abt



Features shown are subject to change without notice

1980 mm 223 Kg 230 Mm

ACCESSORIES







Different tyres and tread profiles



Anti flat tire treatment by polyurethane filled wheels

onestophandling.ie

01 864 9008 info@onestophandling.ie